

Atty Docket No.: JCLA11476-R

Serial No.: 10/695,018

AMENDMENT**In The Claims:**

Please amend the claims in the application according to the following listing of claims.

Claim 1. (currently amended) A chip package structure, at least comprising:

a carrier having a surface, a power pad and a ground pad, said surface having a die bonding area, said power pad and said ground pad being on said surface, said power pad and said ground pad being disposed outside said die bonding area;

a die having an active surface and a backside corresponding to said active surface, said backside being attached to said die bonding area on said surface of said carrier, said die having a plurality of die pads on said active surface;

at least a passive component disposed between said power pad and said ground pad, said passive component having at least two electrodes electrically and physically connected to said power pad and said ground pad respectively; and

at least a first conducting wire having two ends physically connected to one of said plurality of die pads and one of said electrodes, respectively, wherein one of said die pads is electrically connected to said power pad or said ground pad via the first conductive wire and one of said electrodes of said passive component.

Claim 2. (original) The chip package structure of claim 1, further comprising a dielectric material covering said die, said passive component, and said first conducting wire.

Atty Docket No.: JCLA11476-R

Serial No.: 10/695,018

Claim 3. (original) The chip package structure of claim 1, wherein said carrier comprises a signal pad, said signal pad being disposed outside said die bonding area and farther from said die bonding area than said power pad and said ground pad.

Claim 4. (original) The chip package structure of claim 3, further comprising at least a second conducting wire having two ends connected to another one of said plurality of die pads and said signal pad respectively, said second conducting wire crossing over said passive component.

Claim 5. (original) The chip package structure of claim 4, further comprising a dielectric material covering said die, said passive component, said first conducting wire, and said second conducting wire.

Claim 6. (original) The chip package structure of claim 1, wherein the surface of said electrodes comprises a metal layer, said metal layer at least including Ni, Au, or Ni/Au alloy.

Claim 7. (original) The chip package structure of claim 1, wherein said passive component is selected from one of an inductor and a capacitor.

Claim 8. (original) The chip package structure of claim 1, wherein said carrier is a package substrate.

Claim 9. (currently amended) A wire bonding package structure for electrically connecting a die to a carrier, said carrier having a surface and a die bonding area on said surface, said die having an active surface and a backside corresponding to said active surface, said backside of said die being attached to die bonding area, said wire bonding package structure at least comprising:

Atty Docket No.: JCLA11476-R

Serial No.: 10/695,018

a power pad on said surface of said carrier;

a ground pad on said surface of said carrier;

a signal pad on said surface of said carrier, said power pad, said ground pad and said signal pad being disposed outside said die bonding area, wherein said signal pad being farther from said die bonding area than said power pad and said ground pad;

a passive component disposed between said power pad and said ground pad, said passive component having at least two electrodes electrically and physically connected to said power pad and said ground pad respectively;

a plurality of die pads on said active surface of said die;

a first conducting wire having two ends electrically and physically connected to one of said die pads and one of said electrodes respectively; and

a second conducting wire having two ends electrically and physically connected to another one of said die pads and said signal pad respectively, wherein said second conducting wire crossing over said passive component, wherein one of said die pads is electrically connected to said power pad or said ground pad via the first conductive wire and one of said electrodes of said passive component.

Claim 10. (original) The wire bonding package structure of claim 9, wherein the surface of said electrodes comprises a metal layer, said metal layer at least including Ni, Au, or Ni/Au alloy.

Claim 11. (original) The wire bonding package structure of claim 9, wherein said passive component is selected from one of an inductor and a capacitor.

Atty Docket No.: JCLA11476-R

Serial No.: 10/695,018

Claim 12. (original) The wire bonding package structure of claim 9, further comprising a dielectric material covering said die, said passive component, said first conducting wire, and said second conducting wire.

Claim 13. (original) The wire bonding package structure of claim 9, wherein said carrier is a package substrate.

Claim 14. (currently amended) A chip package structure, at least comprising:

a carrier having a surface, a power pad and a ground pad, said surface having a die bonding area, said power pad and said ground pad being on said surface, said power pad and said ground pad being disposed outside said die bonding area;

a die having an active surface and a backside corresponding to said active surface, said backside being attached to said die bonding area on said surface of said carrier, said die having a plurality of die pads on said active surface;

at least a passive component disposed between said power pad and said ground pad, said passive component having at least two electrodes connected to said power pad and said ground pad respectively; and

at least a single first conducting wire having two ends physically connected to one of said plurality of die pads and one of said electrodes, respectively, wherein one of said die pads is electrically connected to said power pad or said ground pad via the first conductive wire and one of said electrodes of said passive component.

Claim 15. (previously presented) The chip package structure of claim 14, wherein said carrier comprises a signal pad, said signal pad being disposed outside said die bonding area and

Atty Docket No.: JCLA11476-R

Serial No.: 10/695,018

farther from said die bonding area than said power pad and said ground pad.

Claim 16. (previously presented) The chip package structure of claim 15 further comprising at least a second conducting wire having two ends connected to another one of said plurality of die pads and said signal pad respectively.

Claim 17. (currently amended) A wire bonding package structure for electrically connecting a die to a carrier, said carrier having a surface and a die bonding area on said surface, said die having an active surface and a backside corresponding to said active surface, said backside of said die being attached to die bonding area, said wire bonding package structure at least comprising:

- a power pad on said surface of said carrier;

- a ground pad on said surface of said carrier;

- a signal pad on said surface of said carrier, said power pad, said ground pad and said signal pad being disposed outside said die bonding area, wherein said signal pad being farther from said die bonding area than said power pad and said ground pad;

- a passive component disposed between said power pad and said ground pad, said passive component having at least two electrodes electrically and physically connected to said power pad and said ground pad respectively;

- a plurality of die pads on said active surface of said die;

- a first single conducting wire having two ends physically connected to one of said die pads and one of said electrodes respectively; and

- a second single conducting wire having two ends physically connected to another one of

Atty Docket No.: JCLA11476-R

Serial No.: 10/695,018

said die pads and said signal pad respectively, wherein said second conducting wire crossing over said passive component, wherein one of said die pads is electrically connected to said power pad or said ground pad via the first conductive wire and one of said electrodes of said passive component.

Claim 18. (previously presented) The wire bonding package structure of claim 17, wherein said passive component is selected from one of an inductor and a capacitor.

Claim 19. (previously presented) The wire bonding package structure of claim 17, further comprising a dielectric material covering said die, said passive component, said first conducting wire, and said second conducting wire.